

RoomPanel Plus Black Datasheet

Multifunctional Meeting Room Scheduling Panel

Yealink RoomPanel Plus Black is a 10.1-inch multifunctional meeting room schedule panel that runs Android 11 and comes with full RGB programmable LED background illumination for immediately visible communication of room status. It includes multi-point touch capability, face recognition camera, built-in NFC/RFID reader, enhanced microphone arrays and speakers to meet the diverse needs of the current office environment. Yealink RoomPanel Plus Black can act as a stand-alone gateway, connect to meeting room sensors and automatically update meeting room schedules, providing various meeting room management functions. Also equipped with Powerover- Ethernet and various mounting brackets, Yealink RoomPanel Plus Black could be easily mounted on any surface.



Key features and benefits

- 10.1-Inch Multi-Point Interactive Panel: Multi-Point touch capability screen to easily book rooms or check-in/out at RoomPanel Plus Black.
- Face Recognition Camera *: Enhanced face recognition security and check-in function.
- High Visibility LED Bars out Room Status: Full RGB LED bars for immediate all-around visible communication of room status.



- Ambient Light & Proximity Sensor Embedded: Environment self-adaptation. Automatically adjust the screen brightness and automatically wake up the screen.
- Various Mounting Methods: Supporting accessories such as no inclination or 20-degree inclination, mullion hangers, 3M glue, etc.
- Orientation Optional *: Easy to mount with portrait or landscape.
- PoE or DC Power: Minimalist and flexible installation, keep workspace tidy and modern.
- Remote Device Management: Easily monitor, manage, and diagnose by Yealink Management Cloud Server.
- WiFi&BLE5.2: Support using the wireless protocol to connect the front-end network and RoomSensor.
- RFID & NFC Embedded *: Enhance ID authorization security and track meeting attendees.
- Actions with Occupancy Sensor *: Actions with the room occupancy sensor, such as automatic release, automatic check-in, etc.
- Extensive APP compatibility: Support the integration of third-party APP applications.

Specifications

| Parameter | Description |
|-----------|--|
| Basic | Operating System: Android 11 Power Supply: Power over Ethernet (IEEE 802.3af/at) DC 12V /1.25A |
| Display | Size(in): 10.1" LCD Panel Resolution: 1280x800 Touch Screen: 10 points capacitive multitouch Contrast: 1000:1 Viewing Angle: ±90° Anti-Fingerprints: Anti-fingerprint Coating |
| Sensors | Ambient Light Sensor TOF Proximity Sensor |
| Camera | Pixel: 2 million pixels |

^{*}Subject to the functions of the third-party APP.



| Connectivity | · 1 x Fast ethernet port(10/100Mbps) |
|---------------|---|
| | · Network: |
| | -Wired network: IEEE 802.1x: |
| | EAP-MD5 |
| | EAP-TLS |
| | EAP-PEAP/MSCHAPv2 |
| | EAP-TTLS/EAP-MSCHAPv2 |
| | -Wi-Fi: 802.11a/b/g/n/ac |
| | · Bluetooth: 5.0 |
| | · RFID/NFC: 13.56MHz |
| | · USB: 1 x USB-A port |
| | · Button: 1 x Reset pinhole |
| Audio | · Microphone: 2 x Microphone |
| Audio | · Speaker: 2 x Speaker |
| | · Angle: No inclination or 20 degree inclination |
| | · Method: Wall, glass or side mount |
| Mounting | - 0° Mount Bracket |
| | - 20° Mount Bracket |
| | - Mullion Mount Bracket |
| Environmental | · Operating Temperature: 0~40°C |
| Environmental | · Operating Humidity: 10~95%, non-condensing |
| Dimensions | · Display size (mm): 247.6 x 166.36 (9.75" x 6.55") |
| Difficusions | · Weight: 0.627 Kg (1.38 lb) |

Supported Platforms

| Platform | |
|--------------|--|
| eams | |
| oom | |
| iingco | |
| iobright | |
| lowscape | |
| pace Connect | |
| ppspace | |

For more information, please go to the Yealink official website.